

XZ-NVR9104T/ XZ-NVR9108T

- ◆ Support megapixel HD network video preview, storage and playback;
- ◆ Click any area and zoom in or zoom out on the image by mouse;
- ◆ Support digital zooming under preview and playback modes;
- ◆ Support search, playback and backup by event;
- ◆ Support 4ch playback simultaneously.



- ◆ Preview channel can be switched to other channel randomly without changing the MAC which is convenient for the project construction;
- ◆ The dendritic menu can be moved. Man-machine communication is more direct and the settings of parameters are more easy and convenient;
- ◆ The mouse roller can realize 15X digital zooming which the enlarged image can be dragged and moved randomly under preview and playback modes;
- ◆ Immediate snapshot and immediate view; the picture will be stored in an independent area in the HDD;
- ◆ The recording playback is shown by time bar and different color represents different recording type. It is very fast and easy to find check the recording;
- ◆ Recording backup can be accurate to second. Any time period of backup is available;
- ◆ The recording files in the USB disk can play directly in the playback interface while the snapshot pictures can be viewed directly;
- ◆ Standard resolution which can be adjusted according to the display device in order to get the best image quality;

Parameters:

Model Number	XZ-NVR9104T	XZ-NVR9108T
Operating System	Embedded LINUX operating system	
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional	
Dual Stream	Each channel can set main stream and sub stream	
Video Standard	1080P(1920×1080)30fps / 960P(1280×960)/720P(1280×720)30fps	
Monitoring Image Quality	1080P(1920×1080) / 960P(1280×960)/ 720P(1280×720)	
Image Motion Detection	Each screen can set mutple detection areas and set 6-level sensitivity(IPC Support) sensitivity (IPC Support)	
Recording Playback Quality	Any 4ch 1080P/960/720P playback simultaneously	
Region Cover	Every channel can set 4 cover regions(IPC Support)	
Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode record mode	
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW network storage and backup(Partly needs IPC Support) network storage and backup (Partly needs IPC Support)	

Operation Way		Mouse, keyboard controller;	
Local Login		User name and password	
Recording Storage		Local HDD, network	
External Ports	Video Input	4×(1920*1080) IP camera	8×(1920*1080) IP camera
	Audio Input	N/A	8ch network audio input
	Video Output	1ch VGA	1ch VGA+1ch HDMI
	Audio Output Output	N/A	1ch auxiliary output
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port	
	USB Port	2 USB 2.0 ports	
HDD	HDD Port	1 SATA HDD ports	
	MAX Capacity	Unlimited for every port	
Mobile Surveillance		Support(iPhone,Android) smart phone	
Power Supply		12V 2A	
Power Consumption		≤30W (without HDD)	
Working Temperature		-10℃~+55℃	
Working Humidity		10%-90%	
Dimension		type: 260mm×230mm×45mm, Packing: 385mm×120mm×65mm	
Weight(without HDD)		N.W.: 1.5Kg; With packing: 2.2Kg	
Installation Way		Desktop Installation, Standard Cabinet Installation	